

Agregáty delíme do skupín :

s pohonom od motora vozidla – typ B a V (vozidlá Pick Up, Van, menšie skriňové rozvážkové vozidlá

THERMO KING		30°C teplota okolia		 m³/h	 m		 kg						
		-20°C [W]	0°C [W]		-20°C	+6°C							
V-700 MAX	R404A	3700	6800	2750	6	8	-	160	-	ANO	-	-	-
V-500 MAX r.	R404A	2870	5630	2400	5	6,5	68	140	-	+	+	+	-
V-500 (recip.)	R134a	1685	4026	2400	3	5,5	68	140	-	-	-	-	-
V-500 MAX	R404A	2700	5020	2400	4,5	6	68	140	-	+	+	+	-
V-500	R134a	1480	3510	2400	3	5	68	140	-	-	-	-	-
V-400 MAX	R404A	2300	4130	1450	3	4	68	140	-	+	-	-	-
V-300 MAX	R404A	1900	3390	1300	17	28	68	93	-	+	+	+	-
V-300	R134a	1300	2865	1300	10	27	68	93	-	-	-	-	+
V-200 MAX	R404A	1480	2650	1100	12	21	-	83	-	+	+	+	-
V-200	R134a	1055	2205	1100	8	18	-	83	-	-	-	-	+
V-100 MAX	R404A	911	1925	680	7	15	59	-	-	+	-	-	-
V-100	R134a	545	1405	680	4	14	59	-	-	-	-	-	-
C-300	R134a	-	2865	1300	-	27	56	-	-	-	-	-	-
C-200	R134a	-	2205	1100	-	18	53	-	-	-	-	-	-
C-100	R134a	-	1045	680	-	10	46	-	-	-	-	-	-
B-100	R134a	390	1050	680	2,5	7	56	68	-	-	-	-	-

s vlastným nezávislým pohonom dieselového motora – typ T a UT (vozidlá strednej a vyššej hmotnostnej kategórie)

THERMO KING		30°C teplota okolia		 m³/h	 El.pripojka (W)		 kg					
		-20°C [W]	0°C [W]		-20°C	0°C						
T-1200R	R404A	6900	11500	330	5300	8900	480	530	-	std	+	+
T-1000R	R404A	5200	8700	3200	4200	6400	470	520	-	std	+	+
T-800R	R404a	4250	7500	2700	3300	5900	450	470	-	std	+	+
T-600R	R404A	3800	6000	2700	3200	4600	450	470	-	std	+	+
UT-1200X	R404a	6900	11400	4000	5400	8000	-	610	-	std	+	+

UT ... agregát so spodnou montážou, s externými výparníkmi s-3 + S-3, resp. UTS-E

návesové agregáty – SLX, SLX Spectrum (návesy)

THERMO KING		30°C teplota okolia		 m³/h	 El.pripojka (W)		 kg					
		-20°C [W]	0°C [W]		-20°C	0°C						
SLX-400	R404a	9200	17500	5500	6900	12400	792	850	-	std	-	-
SLX-300	R404a	8120	15030	5000	6130	11670	790	850	-	std	-	-
SLX-200	R404a	7900	13200	5000	6300	9900	790	845	-	std	-	-
SLX-100	R404a	5900	9500	4250	5500	8200	764	819	-	std	-	-
SLX Spectrum	R404a	9360	16740	4000	6850	11160	790	830	-	std	S2, S3	S2,S3

SLX-Spectrum..... multiplotný agregát s 2mi – 3mi teplotnými zónami i v kombinácii